

SPECIFICATIONS

Item	Standard	Unit	Requirement	Result
Total Thickness	EN428	mm	-----	4.0
Wear Layer	EN429	mm	-----	0.3
Total Weight	EN430	KG/M ²	-----	8.2
Surface Treatment	-----	-----	-----	Deep Emboss - PUR treatment
Size (LxW)	EN427	mm		1220 X 228

TECHNICAL CHARACTERISTICS

Item	Standard	Unit	Result
Peeling Strength of Layer	EN429	---	>50N/50mm
Sound, Impact and Reduction	EN ISO 717-2	dB	>4.8
Fire Resistance	EN13501-1	---	Bfl-S1
Dimension Stability After Exposure to Heat	EN434	%	<0.1
Colour Fastness to Light	EN ISO 105-B02	---	grade>6
Flexibility	EN435	---	Pass
Abrasion Resistance	EN660	---	Class T
Castor Chair Resistance	EN425	---	Pass
Slip Resistance	EN13893	---	>0.3
Chemical Resistance	EN423	---	Pass
Warranty	----	---	Residential – 25 years
			Commercial – Moderate / General use 5 years
Waterproof	----	---	100%

VOC (volatile organic compound) requirements by DIBT from Europe (Germany) for use in residential & commercial environments & contributes to good IAQ (indoor air quality).

